

	VP01 (ACC Hardwire Kit)	VP02 (Hardwire Kit)	VP03 (ACC Hardwire Kit)	VP04 (OBD Hardwire Kit) with LED Screen	VP05 (ACC Hardwire Kit) with LED Screen
Applicable Model	N5/N4 PRO/S1 PRO E3/E2/E1/E1 LITE N2S/N2 PRO/N1 PRO S2/X4S DUO/X4/T3	N5/N4 PRO/S1 PRO E3/E2/E1/E1 LITE N2S/N2 PRO/N1 PRO S2/X4S DUO/X4/T3	N5/N4 PRO/S1 PRO E3/E2/E1/E1 LITE N2S/N2 PRO/N1 PRO S2/X4S DUO/X4/T3	N5/N4 PRO/S1 PRO E3/E2/E1/E1 LITE N2S/N2 PRO/N1 PRO S2/X4S DUO/X4/T3	N5/N4 PRO/S1 PRO E3/E2/E1/E1 LITE N2S/N2 PRO/N1 PRO S2/X4S DUO/X4/T3
Input Voltage	DC 12-24V	DC 12-24V	DC 12-24V	DC 12-24V	DC 12-24V
Output Voltage	DC 5V 2.8A	DC 5V 2A	DC 5V 2A	DC 5V 2.5A	DC 5V 2.5A
Low Voltage Protection Setting	12V vehicle: 11.6V/11.9V/12.2V/12.5V 24V vehicle: 23.6V/23.9V/24.2V/24.5V	12V vehicle: 11.6V/12V 24V vehicle: 23.2V/24V	12V vehicle: 11.6V/12V 24V vehicle: 23.2V/24V	12V vehicle: 11.6V/12V/12.4V 24V vehicle: 23.6V/24V/24.4V	12V vehicle: 11.6V/12V/12.4V 24V vehicle: 23.6V/24V/24.4V
ACC Function	Support	Not Support	Support	Not Support	Support
Working Time	1 hour 3 hours 6 hours 12 hours 24 hours Always	Always	Always	Always	Always
Fuse Adapters	8PCS 2pcs ATO(Regular) fuse 2pcs Mini fuse 2pcs Low-profile Mini fuse 2pcs Micro 2 fuse	4PCS 1pc ATO(Regular) fuse 1pc Mini fuse 1pc Low-profile Mini fuse 1pc Micro 2 fuse	8PCS 2pcs ATO(Regular) fuse 2pcs Mini fuse 2pcs Low-profile Mini fuse 2pcs Micro 2 fuse	OBD	8PCS 2pcs ATO(Regular) fuse 2pcs Mini fuse 2pcs Low-profile Mini fuse 2pcs Micro 2 fuse
Connector	Type C USB Straight Head	Type C USB Straight Head	Type C USB Straight Head	Type C USB Bent Head	Type C USB Bent Head
Cable Length	Input 1m + Output 3.5m	Input 1m + Output 2.5m	Input 1m + Output 2.5m	Input 1m + Output 2.5m	Input 1m + Output 2.5m